



# GLOCK 20 Gen5/MOS/FS



**FRONT SIGHT**  
polymer



**SLIDE STOP LEVER**  
ambidextrous

**TRIGGER CONFIGURATION**  
triggerspring01 / connector 5 /  
firing pin spring 24N (silver)



**REAR SIGHT**  
polymer



**MAGAZINE**  
15 rds



**MAGAZINE CATCH**  
reversible



**PERFECTION**

Technical data are rounded and do not reflect any tolerances – they may be altered without notice.

[www.glock.com](http://www.glock.com)



## TECHNICAL DATA



**CALIBER**

10mm Auto



**MAG. CAPACITY**

15 rds



**BARREL PROFILE**

hexagonal



**BARREL LENGTH**

mm in.  
117 4,61



**LENGTH OF TWIST**

mm in.  
250 9,84



**WEIGHT**

without magazine  
g oz  
755 26,63



**WEIGHT**

with empty magazine  
g oz  
845 29,81



**WEIGHT\***

with loaded magazine  
g oz  
1100 38,80



**TRIGGER TRAVEL**

mm in.  
12,5 0,49

**TRIGGER PULL**

N lbf  
26 5,8

\* depending on the ammunition used

## DIMENSIONS

	mm	in.
1. LENGTH (OVERALL)	205	8,07
2. SLIDE LENGTH (cpl.)	191	7,52
3. WIDTH (OVERALL)	35	1,38
4. SLIDE WIDTH	28,5	1,12
5. HEIGHT INCL. MAGAZINE	140	5,51
6. SIGHT RADIUS (POLYMER)	176	6,93
SIGHT RADIUS (STEEL)	175	6,89
SIGHT RADIUS (GNS)	174	6,85
7. TRIGGER DISTANCE	72,5	2,85
8. BARREL DISTANCE	20	0,79

## VARIABLE DIMENSIONS

		mm	in.
MEDIUM BACKSTRAP w/o beaver tail (+ 2 mm   0.08 in.)	1. LENGTH (OVERALL)	207	8,15
	7. TRIGGER DISTANCE	74,5	2,93
LARGE BACKSTRAP w/o beaver tail (+ 4 mm   0.16 in.)	1. LENGTH (OVERALL)	209	8,23
	7. TRIGGER DISTANCE	76,5	3,01